ISSUE DATE: .56 [14.30] - 6.72 [170.69] -3.99 [101.22] .76 [19.41] -> OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS 6.50 [165.10] (4) POLYCARBONATE FEET .10 [2.54] 3.50 [88.90] **BACK VIEW** 3.99 [101.32] (4) EACH #10-32 BRASS INSERTS, AND STAINLESS STEEL FLANGE AND **FEET SCREWS** 7.47 [189.68] 3.50 [88.90] 5.20 [131.98] 6.75 [171.44] STAINLESS STEEL (4) Ø.31 [7.95] **HINGE PIN** FRONT VIEW WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL → 4.91 [124.65] < NEOPRENE NONMETALLIC → 4.81 [122.24] < LOCKABLE SNAP LATCH LOCATED ON CENTER **GASKET** 6.04 [153.40] 4.81 [122.24] - .13 [3.30] 4.25 [107.95] MUNICIPAL TRANSPORT AND AND ADDRESS AND AD (4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664NLW THIS MATERIAL IS OWNED BY THE ALLIED MOULDED PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE AND IS NOT TO BE REPRODUCED OR DISTRIBUTED

CLEAR COVER AND WINDOWS- POLYCARBONATE

WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.