

Series CT7N Bimetallic Overload Relays

Choose CT7N overloads
in DC applications and
when monitoring Variable
Frequency Drives



Sprecher + Schuh provides
outstanding motor protection with
our CT7N Bimetallic Overload Relay

Sprecher + Schuh has always paid particular attention to the subject of motor protection. This concern is reflected in our CT7N line of thermal overload relays which include many standard features not available with the eutectic alloy overload blocks and heater elements of the past.

Consistent and reliable protection

The consistent high quality of Sprecher + Schuh thermal overload relays is ensured by a complex, factory current calibration procedure performed on each unit at full operating temperature. Calibration is performed at the largest and smallest current the overload can handle. The accurate time/current characteristic curve obtained in this manner guarantees reliable motor protection every time.

Superior Class 10 characteristics

Today's T-Frame motors have less copper and iron than the old U-Frame motors that were popular when traditional Class 20 overload relays were designed. For this reason, faster Class 10 overloads like the CT7N Series have been recognized by many motor manufacturers as the ideal type to assure optimum protection of "T" frame motors with applications involving normal start-up conditions.

Protection from single phase conditions

A unique feature not found in traditional thermal overload relays provides accelerated tripping under single phase conditions. This is accomplished with a special "differential tripping" mechanism built into CT7N (see illustration at right).

Ambient temperature compensation


All Sprecher + Schuh thermal overload relays are temperature compensating. An additional bimetallic ambient compensation strip, built into the conductor-bimetal transmission path, ensures that the tripping characteristics of the relay remain constant over an ambient temperature range of -20°C to $+60^{\circ}\text{C}$.

Single phase applications

CT7N Series thermal overload relays can be applied for protection of single phase AC motors. The relays have the same characteristics as shown for three phase operation. To maintain these characteristics, each element of the overload relay must carry the motor current as shown in the connection diagram on page B2:7.

Other standard features

CT7N bimetallic overload relays feature a selectable reset permitting manual or automatic reset modes. A separate NO signal contact is also provided on CT7N overloads, which is isolated from the NC trip contact. This permits the use of a trip signal voltage different than that of the control voltage. The CT7N is also designed to close-couple connect directly to our CA7 contactors, resulting in a compact package.








CT7N Bimetallic Overload Relays offer accelerated
tripping under single phase conditions

B2

CT7N Overload Relays

CT7N Bimetallic Overload Relays, Manual or Automatic Reset ①④

Overload Relay	Directly Mounts to Contactor...	Adjustment Range (A)②③	Trip Class 10 Catalog Number
 CT7N-23-C16	CA7-9...CA7-23	0.10...0.16	CT7N-23-A16
		0.16...0.25	CT7N-23-A25
		0.25...0.40	CT7N-23-A40
		0.35...0.50	CT7N-23-A50
		0.45...0.63	CT7N-23-A63
		0.55...0.80	CT7N-23-A80
		0.75...1.0	CT7N-23-B10
		0.90...1.3	CT7N-23-B13
		1.1...1.6	CT7N-23-B16
		1.4...2.0	CT7N-23-B20
		1.8...2.5	CT7N-23-B25
		2.3...3.2	CT7N-23-B32
		2.9...4.0	CT7N-23-B40
		3.5...4.8	CT7N-23-B48
		4.5...6.3	CT7N-23-B63
		5.5...7.5	CT7N-23-B75
		7.2...10	CT7N-23-C10
		9.0...12.5	CT7N-23-C12
		11.3...16	CT7N-23-C16
		15...20	CT7N-23-C20
 CT7N-37-C30	CA7-30...CA7-37	15...20	CT7N-37-C20
		17.5...21.5	CT7N-37-C21
		21...25	CT7N-37-C25
		24.5...30	CT7N-37-C30
		29...36	CT7N-37-C36
 CT7N-43-C25	CA7-43...CA7-55	33...38	CT7N-37-C38
		17...25	CT7N-43-C25
		24.5...36	CT7N-43-C36
		35...47	CT7N-43-C47
 CT7N-85-C90	CA7-60...CA7-97	45...60	CT7N-55-C60
		35...47	CT7N-85-C47
		45...60	CT7N-85-C60
		58...75	CT7N-85-C75
		72...90	CT7N-85-C90
 CT7N-97-C97P	Separate mounting required (Panel or DIN-Rail mounted device)	85...97	CT7N-97-C97
		35...47	CT7N-85-C47P
		45...60	CT7N-85-C60P
		58...75	CT7N-85-C75P
		72...90	CT7N-85-C90P
		85...97	CT7N-97-C97P






① CT7N Bimetallic Overload Relays can be used with AC contactors, Electronic DC contactors (CA7-9E...55E) and Two-Winding DC contactors (CA7-60D...97D).

② To select the setting range for use in Wye-Delta Starters, multiply the rated operating current of the motor by a factor of 0.58.



③ For motors with service factor of 1.15 or greater, use motor nameplate full load current. For motors with service factor of 1.0, use 90% of the motor nameplate full load current.

④ Under phase loss condition, this 3-phase two slider bar tripping mechanism will trip in approximately 45 seconds.

Accessories

Component	Description	For Use With...	Catalog Number
	DIN-rail / Panel Mount Adapter - For separately mounting thermal overload relays	CT7N-23..37	CT7N-37-P-A
	Screw Adapter - For screw fixing of the CT7N-37-P-A panel adapter (1 required per adapter) Pkg. of 10.	CT7N-37-P-A	Use KT7-45-AS
	Remote Reset Solenoid - ④⑤ For remote resetting of the overload relay	CT7N ③ CT8 24V AC 50-60Hz 48V AC 50-60Hz 110V 50Hz/120V 60Hz 220-240V 50-60Hz 24V DC 48V DC 110V DC 125V DC	CMR7N-24V50-60 CMR7N-48V50-60 CMR7N-110V50-120V60 CMR7N-220-240V50-60 CMR7N-24VDC CMR7N-48VDC CMR7N-110VDC CMR7N-125VDC
	External Reset Button - Used for manually resetting overloads mounted in enclosures	CT7N all	Use D7 Reset
	Adaptor External Reset - Mounts on relay reset button and provides larger actuation surface.	CT7N ③ CT8	CT7N-RA3

Marking Systems ①

Component	Description	Pkg. Qty.	Catalog Number
	Label Sheet - 1 sheet with 105 self-adhesive paper labels each, 6 x 17mm	1	CA7-FMS
	Marking Tag Sheet - 1 sheet with 160 perforated paper labels each, 6 x 17mm. To be used with transparent cover.	1	CA7-FMP
	Transparent Cover - To be used with Marking Tag Sheets.	100 ②	CA7-FMC

① The labeling field of the overload relay may also be written on by hand.

② Minimum order quantity is one package of 100. Price each x 100 = package price.

③ CMR7N-✱ and CT7N-RA3 will not mount on separate mount versions of CT7N.

④ Coil consumption of AC coils is 8VA.











⑤ Coil consumption of DC coils is 12 watts.

Electrical Data

Main Circuits			CT7N
Rated Insulation Voltage U_i	[V]		690
Rated Impulse Strength U_{imp}			
Between main poles and between main poles & auxiliaries			6
Between auxiliary circuits	[kV]		4
Rated Operating Voltage U_e			
	IEC	[V AC]	690
		[V DC]	440
	UL, CSA	[V AC]	600
		[Hz]	50/60
Rated Frequencies			
Power dissipation			
	up to 0.4 A	[W]	7
CT7N-23...37	0.5...36 A	[W]	6
	38 A	[W]	12
CT7N-43...55	25...47 A	[W]	12
CT7N-85...97	47...90 A	[W]	18
Lifespan			
Stop function, operates the release contact	Mechanical	[Mil. ops.]	0.25
95-96	Electrical, at max. contact rating	[Mil. ops.]	0.25
Trip Class			
		CT7N-23/37	CT7N-43/55/85/97
	IEC/EN 60947-4-1	10A	10
	UL		10
Trip Rating (ultimate tripping current)			125% FLA
Phase Loss Sensitivity: Trip rating at phase loss			115% FLA
Reset mode			Automatic or Manual
Test release			Manual release of auxiliary contacts
Trip indicator			Flag visible through opening on front of relay
Approximate weight (unpackaged)			
	CT7N-23		.115 kg
	CT7N-37-C20...25		.115 kg
	CT7N-37-C30...38		.155 kg
	CT7N-45/55		.330 kg
	CT7N-85		.360 kg
	CT7N-85-_P		.415 kg

Operating Limits		CMR7N
Maximum Command Impulse		5s
AC 50/60Hz	Pick-up [$x U_s$]	0.8...1.1
	Drop-out [$x U_s$]	
DC	Pick-up [$x U_s$]	0.7...1.25
	Drop-out [$x U_s$]	
Coil Consumption		
AC 50/60Hz	Pick-up [VA-W]	
	Hold-in [VA-W]	
	Pick-up [$x U_s$]	17 (24, 110, 125V) 25 (48V)
DC	Pick-up [$x U_s$]	17 (24, 110, 125V) 25 (48V)
	Drop-out [$x U_s$]	

Control Circuits			CT7N
Rated Operating Current I_e			
AC-15	24V	[A]	4
	240V	[A]	2
	400V	[A]	1.6
	690V	[A]	0.15
DC-13	24V	[A]	2
	110V	[A]	0.4
	220V	[A]	0.25
	440V	[A]	0.08
Thermal Current I_{th}			5
Short Circuit withstand, Fuse			IEC, gL/gG [A] 6
Short-circuit withstand, circuit breaker $\leq 1kA$ prospective short-circuit-current			[A] 4
Min. contact load for reliable operation			15V, 2 mA
Approvals			
	UL Rating		A600/Q300
	CSA		C22.2 No. 14
	cULus		E33916, NKCR, NKCR7
	IEC/EN		6094 S7-1, -4-1, -5-1

Terminations		Main Circuits						Control Circuits	Remote Reset
		CT7N-23-A16...C25	CT7N-37-C20...25	CT7N-37-C30...38	CT7N-43-CT7N-55	CT7N-85-CT7N-97	CT7N-37-P-A	CT7N	CMR7N
Terminal Cross-Sections									
Terminal Type									
Terminal Screws		M4	M4	M4	M5	M6	M4	M3.5	M3.5
	Fine stranded with Ferrule	[mm²] 2x (1.5...4)	2x (1.5...4)	1x (2.5...10)	1x (2.5...16)	1x (10...35)	1x (1.5...10)	2x (1...4)	2x (1...2.5)
	Solid or Course Stranded	[mm²] 2x (1.5...6)	2x (1.5...6)	1x (2.5...16)	1x (2.5...25)	1x (10...35)	1x (1.5...16)	2x (1...4)	1x (1...2.5)
		[AWG] 2x (16...10)	2x (14...10)	1x (10...6)	1x (10...6)	1x (8...1)	1x (16...6)	2x (18...12)	1x (16...12)
Recommended Torque		[Nm] 1.5...2.2	1.5...2.2	2.5...3.5	2.5...3.5	4.5...6	1.8...2.8	1.2	1.2
		[lb-in] 13...20	13...20	22...31	22...31	40...53	16...25	10.6	10.6
Pozidrive Screwdriver		Size 2	2	2	2	~	2	2	2
Slotted Screwdriver		mm .8 x 5.5	.8 x 5.5	.8 x 5.5	.8 x 5.5	~	.8 x 5.5	.8 x 5.5	.8 x 5.5
Hexagon Socket Screw		Size ~	~	~	~	4	~	~	~

General Data

CT7N		CT7N	
Type of overload relay	Bimetallic, Ambient Compensated, Phase Loss Sensitive	Environmental	Storage Temp. Range
Compensation temperature range	-20...+60°C (-4...+140°F)		-55...+80°C
Type of Protection in connected state	IP00	Climatic Conditions	Operating Temperature Range
Finger Protection	Safe from touch by fingers and back of hand (VDE 0106, Part 100)		-20...+60°C
Materials	RoHS compliant	Vibration	Air moisture (Storage/Operating)
Flame Resistivity (Outer housing parts)	UL94: V0		5...95% rel. humidity
		Shock	(per IEC/EN 60068-2-6), service
			3g
		Max. Altitude	IEC/EN 61373 (vibration railways)
			cat. 1, class B
		Pollution Degree	IEC/EN 60092-504 (vibration ships). service
			0.7g all axes, 2-200 Hz
			(per IEC/EN 6800-2-27), transport
			30g
			IEC/EN 60068-2-27 (shock half-sinus) service
			11 ms > 5 g
			(per IEC/EN 61373 (shock railways)
			cat. 1, class B

B2
CT7N Overload Relays


Thermal Overload Relay Maximum Fuse

For Use With...	Catalog Number	Adjustment Range (A)	Max. Back-up fuse [A]		
			gL/gG 50 kA, 690V AC IEC/EN 60947-4-1 Coordination		UL Class K5 5 kA, 600V AC
			Type 1	Type 2	UL 508
CA7-9...CA7-23	CT7N-23-A16	0.10...0.16	50	~	1
	CT7N-23-A25	0.16...0.25		~	1
	CT7N-23-A40	0.25...0.40		2	1
	CT7N-23-A50	0.35...0.50		2	2
	CT7N-23-A63	0.45...0.63		2	2
	CT7N-23-A80	0.55...0.80		4	3
	CT7N-23-B10	0.75...1.0		4	3
	CT7N-23-B13	0.90...1.3		6	4
	CT7N-23-B16	1.1...1.6		6	5
	CT7N-23-B20	1.4...2.0		10	8
	CT7N-23-B25	1.8...2.5		16	10
	CT7N-23-B32	2.3...3.2		16	12
	CT7N-23-B40	2.9...4.0		16	15
	CT7N-23-B48	3.5...4.8		16	15
	CT7N-23-B63	4.5...6.3		20	20
	CT7N-23-B75	5.5...7.5		25	25
	CT7N-23-C10	7.2...10		25	35
	CT7N-23-C12	9.0...12.5		35	50
	CT7N-23-C16	11.3...16		35	60
	CT7N-23-C20	15...20	80	40	80
	CT7N-23-C21	17.5...21.5		50	80
	CT7N-23-C25	21...25		50	100
CA7-30...CA7-37	CT7N-37-C20	15...20	80	40	80
	CT7N-37-C21	17.5...21.5		50	80
	CT7N-37-C25	21...25		50	100
	CT7N-37-C30	24.5...30	100	63	100
	CT7N-37-C36	29...36	125	63	125
	CT7N-37-C38	33...38		63	150
CA7-43...CA7-55	CT7N-43-C25	17...25	100	50	100
	CT7N-43-C36	24.5...36	125	80	125
	CT7N-43-C47	35...47	160	100	175
	CT7N-55-C60	45...60	200	125	150
CA7-60...CA7-97	CT7N-85-C47	35...47	160	100	175
	CT7N-85-C60	45...60	200	125	250 ❶
	CT7N-85-C75	58...75	200	125	300 ❶
	CT7N-85-C90	72...90	250	160	350 ❶
Separate mounting required (Panel-mounted device)	CT7N-97-C97	85...97	250	160	250 ❶
	CT7N-85-C47P	35...47	160	100	175 ❷
	CT7N-85-C60P	45...60	200	125	250 ❶❷
	CT7N-85-C75P	58...75	200	125	300 ❶❷
	CT7N-85-C90P	72...90	250	160	350 ❶❷
	CT7N-97-C97P	85...97	250	160	250 ❶❷

❶ Max. Back-up fuse [A], UL Class K5, 10 kA, 600V AC

❷ Only in combination with CA7 Contactors.

Connection Diagrams



B2


CT7N Overload Relays

Tripping Characteristics

These tripping characteristics refer to IEC/EN 60947-1 and are average values from cold start at an ambient temperature of 20°C. Trip time is pictured as a function of operating current. With the device at max. operating temperature, the trip time decreases to approximately 25% of the shown value.


- (a) Tripping characteristics 3-poles from the cold state
- (b) Tripping characteristics 2-poles from the cold state

CT7N-23-A16...A40 Overload Relays




Tripping Characteristics (Continued)


CT7N-23-A50...B40 Overload Relays




CT7N-23-B48...C25 Overload Relays



CT7N-37-C20...C25 Overload Relays




CT7N-37-C30...C38 Overload Relays




Tripping Characteristics (Continued)

CT7N-43-C25...C47 Overload Relays



CT7N-85-C47...C90 Overload Relays




B2

CT7N Overload Relays

Series CT7N (Mounting to CA7 Contactors)


Dimensions are in millimeters (inches). Dimensions not intended for manufacturing purposes.




Contactor + Overload	a	b	b1	c1	c2	c3	ød	e1	e2	f1	f2	g	h	j	k1	k2
CA7-9...23 + CT7N-23-A16...C25	45 (1-25/32)	136.5 (5-3/8)	43 (1-11/16)	81.5 (3-13/64)	80.5 (3-11/64)	5 (13/64)	4.5 (3/16)	37.5 (1-15/32)	55 (2-11/64)	40.5 (1-19/32)	68.5 (2-45/64)	35 (1-3/8)	60 (2-23/64)	63.5 (2-1/2)	29 (1-9/64)	37.5 (1-15/32)
CA7-30...37 + CT7N-37-C20...C25	45 (1-25/32)	136.5 (5-3/8)	43 (1-11/16)	99.5 (3-28/32)	89 (3-1/2)	5 (13/64)	4.5 (3/16)	37.5 (1-15/32)	60.5 (2-3/8)	45.5 (1-51/64)	73 (2-7/8)	35 (1-3/8)	60 (2-23/64)	63.5 (2-1/2)	29 (1-9/64)	37.5 (1-15/32)
CA7-30...37 + CT7N-37-C30...C38	45 (1-25/32)	149 (5-55/64)	43 (1-11/16)	99.5 (3-28/32)	89 (3-1/2)	5 (13/64)	4.5 (3/16)	37.5 (1-15/32)	60.5 (2-3/8)	47 (1-27/32)	73 (2-7/8)	35 (1-3/8)	60 (2-23/64)	63.5 (2-1/2)	29 (1-9/64)	37.5 (1-15/32)
CA7-43 + CT7N-43-C25...C47	54 (2-1/8)	149 (5-55/64)	43 (1-11/16)	102 (4-1/64)	100 (3-15/16)	5 (13/64)	4.5 (3/16)	37.5 (1-15/32)	61 (2-13/32)	48 (1-57/64)	88 (3-15/32)	45 (1-25/32)	60 (2-23/64)	66.5 (2-5/8)	34 (1-11/32)	42.5 (1-43/64)
CA7-55 + CT7N-55-C60	54 (2-1/8)	149 (5-55/64)	43 (1-11/16)	102 (4-1/64)	100 (3-15/16)	5 (13/64)	4.5 (3/16)	37.5 (1-15/32)	61 (2-13/32)	48 (1-57/64)	88 (3-15/32)	45 (1-25/32)	60 (2-23/64)	66.5 (2-5/8)	34 (1-11/32)	42.5 (1-43/64)
CA7-60...85 + CT7N-85-C47...C90	72 (2-53/64)	191 (7-33/64)	64 (2-33/64)	120 (4-23/32)	108 (4-1/4)	5.5 (7/32)	5.4 (7/32)	45 (1-25/32)	74 (2-29/32)	55.5 (2-3/16)	80 (3-5/32)	55 (2-11/64)	100 (3-15/16)	87.5 (3-7/16)	41.5 (1-41/64)	50 (1-31/32)
CA7-97 + CT7N-97-C97	72 (2-53/64)	191 (7-33/64)	64 (2-33/64)	120 (4-23/32)	108 (4-1/4)	5.5 (7/32)	5.4 (7/32)	45 (1-25/32)	74 (2-29/32)	55.5 (2-3/16)	80 (3-5/32)	55 (2-11/64)	100 (3-15/16)	87.5 (3-7/16)	41.5 (1-41/64)	50 (1-31/32)

Series CT7N Separate Mount (+ Adaptor)

Dimensions are in millimeters (inches). Dimensions not intended for manufacturing purposes.




CT7N-23..37 with Panel Mount Adapter



CT7N-85...97 Separate Mount

Overload + DIN Rail/Panel Mounting Adapter	a	b	b1	c1	c2	c3	ød	e1	f1	f2	g	h	k1	k2
CT7N-23-A16...C25 + CT7N-37-P-A CT7N-37-C20...C25 + CT7N-37-P-A	45 (1-25/32)	89.5 (3-17/32)	50 (1-31/32)	69 (2-23/32)	66 (2-19/32)	4 (5/32)	4.5 (3/16)	38 (1-31/64)	26 (1-1/32)	54 (2-1/8)	15 (19/32)	90 (3-35/64)	29 (1-9/64)	37.5 (1-15/32)
CT7N-37-C30...C38 + CT7N-37-P-A	45 (1-25/32)	91.5 (3-39/64)	50 (1-31/32)	69 (2-23/32)	66 (2-19/32)	4 (5/32)	4.5 (3/16)	38 (1-31/64)	28 (1-7/64)	54 (2-1/8)	15 (19/32)	90 (3-35/64)	29 (1-9/64)	37.5 (1-15/32)
CT7N-85-C47P...CT7N-97-C97P	56 (2-13/64)	82 (3-15/64)	46 (1-13/16)	99.5 (3-28/32)	~	4 (5/32)	4.5 (3/16)	56 (2-13/64)	47.5 (1-7/8)	87 (3-27/64)	~	60 (2-23/64)	41.5 (1-41/64)	50 (1-31/32)

CT7N-RA3 External Reset Adaptor



CMR7N Remote Reset Solenoid

