



Product designation			Double-touch actuators, spring return - two flush pushbuttons	
Product type designation			LPCB7191+LPXAU12	
General characteristics				
Colour			Black/Black	
Type of positions			Double-touch with two flush pushbuttons	
IEC degree of protection			IP66, IP67 and IP69K	
Electrical characteristics				
Rated insulation voltage Ui IEC/EN		V	690	
IEC Conventional free air thermal current Ith		A	10	
Conductivity		1mA 5V		
UL/CSA and IEC/EN 60947-5-1 designation		A600 Q600		
Operating current AC15		12V	A	6
		24V	A	6
		48V	A	6
		120V	A	6
		240V	A	3
		400V	A	1.9
		480V	A	1.5
		500V	A	1.4
		600V	A	1.2
Operating current DC13		12V	A	3
		24V	A	3
		48V	A	1.5
		125V	A	0.55
		250V	A	0.27
		440V	A	0.15
		500V	A	0.13
		600V	A	0.1
Contact resistance		mΩ	≤20	
Mechanical features				
Operating force		kg-lb	<0.5Kg / 1.1lb	
Mechanical life		cycles	1000000	
Terminals screw		Screw		
Conductor section		IEC		
		max	mm²	1 or 2 / 2.5
Mounting adapter		LPXAU120		
UL technical data				
UL degree of protection		Type1, 2, 3R, 4, 4X, 12, 12K		
Ambient conditions				
Temperature		Operating temperature		
		min	°C	-25
		max	°C	+70
Storage temperature				
		min	°C	-40
		max	°C	+85
Certifications and compliance				

KIT PLASTIC DOUBLE-TOUCH ACTUATOR, SPRING RETURN, 2 FLUSH PUSHBUTTONS,
BLACK BLACK/↑ ↓ WITH MOUNTING ADAPTER AND 2 CONTACT ELEMENTS, 2NO. SCREW
TERMINATION

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

Certificates

CCC

cULus

EAC

RINA