



Triple-touch actuators,
spring return - One
middle extended
buttons
LPCB7355+LPXAU120

Product designation

Product type designation

General characteristics

Colour	Green/Red/Green		
Type of positions	Triple-touch		
IEC degree of protection	IP66, IP67 and IP69K		
Electrical characteristics			
Rated insulation voltage Ui IEC/EN	V	690	
IEC Conventional free air thermal current Ith	A	10	
Conductivity	1mA 5V		
UL/CSA and IEC/EN 60947-5-1 designation	A600 O600		

Operating current AC15

12V	A	6
24V	A	6
48V	A	6
120V	A	6
240V	A	3
400V	A	1.9
480V	A	1.5
500V	A	1.4
600V	A	1.2

Operating current DC13

12V	A	3
24V	A	3
48V	A	1.5
125V	A	0.55
250V	A	0.27
440V	A	0.15
500V	A	0.13
600V	A	0.1

Contact resistance	mΩ	≤20	
--------------------	----	-----	--

Mechanical features

Mechanical Features		
Operating force	kg-lb	<0.5Kg / 1.1lb
Mechanical life	cycles	1000000
Terminals screw	Screw	
Conductor section		

Conductor section

IEC

max	mm²	1 or 2 / 2.5
-----	-----	--------------

Mounting adapter	LPXAU120		
------------------	----------	--	--

UL technical data

UL degree of protection	Type1, 2, 3R, 4, 4X, 12, 12K		
-------------------------	------------------------------	--	--

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+70

Storage temperature

min	°C	-40
max	°C	+85

Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN/BS 60947-1
IEC/EN/BS 60947-5-1
UL508

Certificates

CCC

KIT PLASTIC TRIPLE-TOUCH ACTUATOR, SPRING RETURN, 2 EXTERNAL FLUSH AND 1
MIDDLE EXTENDED PUSHBUTTONS. SPRING RETURN, ↑ STOP ↓ WITH MOUNTING
ADAPTER AND 2 CONTACT ELEMENTS, 2NO+1NC. SCREW TERMINATION

cULus

EAC

RINA