



Double-touch
actuators, spring
return - One
extended and
one flush
pushbuttons
LPSB72

Product designation

Product type designation


General characteristics

Colour	White/Black	
Type of positions	Double-touch with one extended and one flush pushbuttons	
Material	Aluminium and zinc alloy for metal parts and polyamide for plastic parts	
IEC degree of protection	IP66, IP67 and IP69K	
Mechanical features		
Mechanical life	cycles	1000000
Fixing	Without mounting adapter	
Mounting adapter	LPXAU120M	
UL technical data		
UL degree of protection	Type1, 2, 3R, 4, 4X, 12, 12K	

Ambient conditions

Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
	max	°C	+85

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14

DOUBLE-TOUCH ACTUATOR, SPRING RETURN Ø22MM PLATINUM SERIES METAL, 1
EXTENDED AND 1 FLUSH PUSHBUTTONS. BOTH SPRING RETURN, WHITE - BLACK

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

ETIM classification

ETIM 8.0

EC000029 -
Push-switch
button