



Double-touch
actuators, spring
return white
indicator - Two
flush pushbuttons
LPSBL71

Product designation

Product type designation

General characteristics

| | |
|--------------------------|--|
| Colour | Black/Red |
| Type of positions | Double-touch with two flush pushbuttons |
| Material | Aluminium and zinc alloy for metal parts and polyamide for plastic parts |
| IEC degree of protection | IP66, IP67 and IP69K |

Mechanical features

| | | |
|------------------|-----------------------------|---------|
| Mechanical life | cycles | 1000000 |
| Fixing | Without mounting adapter | |
| Mounting adapter | LPXAU120M | |

UL technical data

| | |
|-------------------------|---------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|---------------------------------|

Ambient conditions

Temperature


Operating temperature

| | | |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +70 |

Storage temperature

| | | |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +85 |

Dimensions



Certifications and compliance

Compliance

| |
|---------------------|
| CSA C22.2 n° 14 |
| IEC/EN/BS 60947-1 |
| IEC/EN/BS 60947-5-1 |

UL508

Certificates

cULus

ETIM classification

ETIM 8.0

EC000221 -
Front element for
push button