



Product designation

RF82

Product type designation

Motor protection  
relay

### General characteristics

|                         |          |         |
|-------------------------|----------|---------|
| Number of poles         | Nr.      | 3       |
| Overvoltage category    |          | III     |
| Pollution degree        |          | 3       |
| Frontal IP degree       |          | IP20    |
| Type of release         |          | Thermal |
| Protection fuse         |          |         |
|                         | gG (IEC) | A 125   |
|                         | aM (IEC) | A 80    |
|                         | K5 (UL)  | A 200   |
| Phase failure detection |          | yes     |
| Reset mode              |          | Manual  |

### Power circuit characteristics

|                                           |                         |                      |
|-------------------------------------------|-------------------------|----------------------|
| Rated insulation voltage $U_i$ IEC/EN     | V                       | 690                  |
| Rated impulse withstand voltage $U_{imp}$ | kV                      | 8                    |
| Rated operational voltage                 | V                       | 690                  |
| Operational frequency                     | min<br>max              | Hz<br>Hz<br>0<br>400 |
| Operational current $I_e$                 |                         |                      |
|                                           | Operational current min | A 46                 |
|                                           | Operational current max | A 65                 |
| Tripping class                            |                         | 10A                  |
| Test Button                               |                         | Yes                  |
| Trip indicator                            |                         | yes                  |

Terminals

type  
screw  
width  
tool  
mm  
Yoke clamp  
M5  
9  
Phillips 2

Tightening torque for terminals

min  
max  
min  
max  
Nm  
Nm  
lbin  
lbin  
3.9  
3.9  
2.88  
2.88

Conductor section

AWG/kcmil max 2

### Auxiliary circuit characteristics


Auxiliary contacts

NO  
NC  
Nr.  
Nr.  
1  
1


Auxiliary Rated insulation voltage  $U_i$  IEC/EN

V 690

|                                                  |                                        |                                    |
|--------------------------------------------------|----------------------------------------|------------------------------------|
| Auxiliary Rated impulse withstand voltage Uimp   | kV                                     | 6                                  |
| Auxiliary Rated operational voltage              | V                                      | 690                                |
| Operating current AC15                           | 24V                                    | A 3                                |
|                                                  | 120V                                   | A 3                                |
|                                                  | 240V                                   | A 1.5                              |
|                                                  | 380V                                   | A 0.95                             |
|                                                  | 480V                                   | A 0.75                             |
|                                                  | 500V                                   | A 0.72                             |
|                                                  | 600V                                   | A 0.6                              |
| Operating current DC13                           | 125V                                   | A 0.11                             |
|                                                  | 600V                                   | A 0.22                             |
| IEC Conventional free air thermal current Ith    | A                                      | 10                                 |
| Terminals                                        | Auxiliary circuit type                 | screw and washer                   |
|                                                  | Auxiliary circuit screw                | M3,5                               |
|                                                  | Auxiliary circuit width                | mm 8                               |
|                                                  | Auxiliary circuit tool                 | Phillips 1                         |
| Conductor section                                | Auxiliary circuit Flexible w/o lug max | mm <sup>2</sup> 2.5                |
|                                                  | Auxiliary circuit Flexible c/w lug max | mm <sup>2</sup> 2.5                |
| Tightening torque for terminals                  | Auxiliary circuit min                  | Nm 1                               |
|                                                  | Auxiliary circuit max                  | Nm 1                               |
|                                                  | Auxiliary circuit min                  | lbin 0.74                          |
|                                                  | Auxiliary circuit max                  | lbin 0.74                          |
| UL/CSA and IEC/EN 60947-5-1 designation          |                                        | B600-P600                          |
| <b>Ambient conditions</b>                        |                                        |                                    |
| Operating temperature                            | min                                    | °C -20                             |
|                                                  | max                                    | °C 55                              |
| Storage temperature                              | min                                    | °C -55                             |
|                                                  | max                                    | °C 80                              |
| Compensation temperature                         | min                                    | °C -15                             |
|                                                  | max                                    | °C 55                              |
| Max altitude                                     | m                                      | 3000                               |
| <b>Mechanical features</b>                       |                                        |                                    |
| Operating position                               | normal allowable                       | Vertical plan ±30°                 |
| Fixing                                           |                                        | Direct mounting on BF40... BF94... |
| Weight                                           | g                                      | 365                                |
| <b>UL technical data</b>                         |                                        |                                    |
| Full-load current (FLA) for three-phase AC motor | at 480V                                | A 65                               |
|                                                  | at 600V                                | A 65                               |
| <b>Dimensions</b>                                |                                        |                                    |



### Wiring diagrams



### Certifications and compliance

#### Compliance

CSA C22.2 n° 14  
IEC/EN 60947-1  
IEC/EN 60947-4-1  
UL508

#### Certifications

cULus

### ETIM classification

ETIM 8.0

EC000106 -  
Thermal overload  
relay