



BS (BS labeling system)




Product information

The BS labeling system consists of various components and is used for subsequent labeling of device locations or switchgear.

- BS 1:consists of the clamping piece BS 3, transparent top and 27 x 8 mm paper strip on a DIN A-4 sheet with perforated edges.
- BS 3:clamping piece for the transparent label holder KM 7 or for the BS 5 label.
- BS 4:consists of the clamping piece BS 3 and the BS 5 label.
- BS 9 / BS 10:label holder for KSS 20x9 labels or for KM 6/18 transparent label holders with KS 4/18 label. Mounting is accomplished with a self-clamping (spring-loaded) foot.

Information, conformities and approvals



Article	Order No.	Color	Area of application from - to Ø mm	Wire cross section from - to mm	Printable area mm	Quantity per sheet	Quantity per frame	Software Article	PU pcs.
BS 3 clamping piece, with transparent top and DIN A4 paper strip									
BS 1	86281010	Black	1.25 - 3.7	0.5 - 2.5					500
DIN A4 paper sheet with punched margin for BS 1									
Paper sheet	86281013	White			8 x 25	256		BS0	2560
Clamping piece: for transparent label holder KM 7 or for label BS 5									
BS 3	86281016	Black	1.25 - 3.7	0.5 - 2.5					190
Clamping piece BS 3 with label BS 5									
BS 4	86281018	Black	1.25 - 3.7	0.5 - 2.5	12 x 27		16	79	190
Label holder (self-clamping): for labels KSS 20x9 or for transparent label holders KM 6/18									
BS 9	86281024	Black	4						50
BS 10	86281026	Black	4 - 11						50



BS (BS labeling system)

Material properties



Polyvinyl chloride (PVC) || Polycarbonate (PC) ||

Thermal properties



Temperature / temperature range -40 °C – 60 °C

Fire properties



Fire classification V0

Classification



ETIM 9: EC001530 || eClass 14: 27281102 || UNSPSC: 39131504 ||

Assembly method



Self-clamping system

Labelling technology



Plotter



Laser



Laser printer



Inkjet



Idents