



KSE label plate




Product information

The KSE label plates are pushed directly onto the single wires.

- Wire cross section from 0.25 - 1.5 mm²
- Available in two sizes
- Available in white

Information, conformities and approvals



Article	Order No.	Color	RAL equiv.	Areas of application from - to in mm (C)	Wire cross section from - to mm ² (D)	Label size mm (B x A)	Printable area (mm)	Number of characters / lines	Quantity per frame	Software Article	Base plate	PU pcs.
---------	-----------	-------	------------	--	--	-----------------------	---------------------	------------------------------	--------------------	------------------	------------	---------

Usable label length 10 mm

KSE 4/10-0.75	86381010	White	9016	1.5 - 2.5	0.25 - 0.75	6 x 18	4 x 10	5 / 1	60	92	GRPD/10	1500
KSE 4/10-1.5	86381012	White	9016	2.5 - 3	0.75 - 1.5	6 x 18	4 x 10	5 / 1	60	93	GRPD/10	1500

Usable label length 18 mm

KSE 4/18-1.5	86381014	White	9016	2.5 - 3	0.75 - 1.5	6 x 26	4 x 18	10 / 1	40	94	GRPD/18	1000
--------------	----------	-------	------	---------	------------	--------	--------	--------	----	----	---------	------

Material properties



Polycarbonate (PC) II

Thermal properties



Temperature / temperature range -40 °C - 130 °C



KSE label plate

Fire properties



Fire classification V0

Technical information



Halogen-free

Classification



ETIM 9: EC001530 || eClass 14: 27281102 || UNSPSC: 39131504 ||

General technical data



Assembly method 010000000000

Assembly method



Direct labeling system

Labelling technology



Plotter



Laser



Inkjet

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.