




Label KNC/ B



Product information

High-quality, halogen-free label for simultaneous double-sided subsequent direct labeling of wires. The KNC/B label, made of PC materials, was developed for the direct and subsequent labeling of cords and cables on the front and back. No tools required.

Available in five sizes for wire cross-sections of 1.6 - 5.7 mm.

Information, conformities and approvals



Article	Order No.	Color	RAL equiv.	Areas of application from - to in mm (C)	Label size mm (B x A)	Printable area (mm)	Number of characters / lines	Quantity per frame	Software Article	Base plate	PU pcs.
---------	-----------	-------	------------	------------------------------------------	-----------------------	---------------------	------------------------------	--------------------	------------------	------------	---------

For cable diameters of 1.6 mm to 2.0 mm

KNC/B 4,0/15-1,0	86382002	White	9016	1.6 - 2	4 x 15	4 x 15	8 / 1	21	C24	GP3C-B	273
KNC/B 4,0/23-1,0	86382006	White	9016	1.6 - 2	4 x 23	4 x 23	12 / 1	21	C25	GP3C-B	273

For cable diameters of 2.0 mm to 2.5 mm

KNC/B 4,0/15-2,0	86382012	White	9016	2 - 2.5	4 x 15	4 x 15	8 / 1	21	C26	GP3C-B	273
KNC/B 4,0/23-2,0	86382016	White	9016	2 - 2.5	4 x 23	4 x 23	12 / 1	21	C27	GP3C-B	273

For cable diameters of 2.9 mm to 3.6 mm

KNC/B 5,5/15-3,0	86382022	White	9016	2.9 - 3.6	5.5 x 15	5.5 x 15	8 / 1	18	C28	GP3C-B	234
KNC/B 5,5/23-3,0	86382026	White	9016	2.9 - 3.6	5.5 x 23	5.5 x 23	12 / 1	18	C29	GP3C-B	234

For cable diameters of 4.1 mm to 4.6 mm

KNC/B 5,5/23-4,0	86382036	White	9016	4.1 - 4.6	5.5 x 23	5.5 x 23	12 / 1	18	C30	GP3C-B	234
------------------	----------	-------	------	-----------	----------	----------	--------	----	-----	--------	-----

For cable diameters of 5.7 mm



Label KNC/ B

Article	Order No.	Color	RAL equiv.	Areas of application from - to in mm (C)	Label size mm (B x A)	Printable area (mm)	Number of characters / lines	Quantity per frame	Software Article	Base plate	PU pcs.
KNC/B 7.2/23-5,086382046		White	9016	5.7 - 5.7	7.2 x 23	7.2 x 23	12 / 2	15	C31	GP3C-B	165

Material properties



Polycarbonate (PC) II

Thermal properties



Temperature / temperature range -40 °C – 130 °C

Fire properties



Fire classification VO

Technical information



Halogen-free

Classification



ETIM 9: EC001530 || eClass 14: 27281102 || UNSPSC: 39131504 ||

General technical data



Assembly method 000001000000

Assembly method



Clamping system

Labelling technology



Plotter



Laser



Label KNC/ B

Labelling technology

	Inkjet
----------------------------------------------------------------------------------	--------

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.