

## KCM-ECO manual cable labeling



### Product information

The KCM-ECO label plates are made of PE composite material on a transparent carrier film and a 3" core. The KCM-ECO plates are used for subsequent labeling of cables and thicker wires with labels and cable ties.

The special feature of the KCM-ECO label plates is the eyelet open on one side for faster feed-through of the cable tie. The cable tie only has to be threaded in on one side.

KCM-ECO label plates for subsequent manual cable labeling are available in sizes 60x12 mm and 75x15 mm in white or yellow.

Suitable for mp-TM series thermal transfer printers.

### Information, conformities and approvals



Article	Order No.	Color	Sheet size Length x width mm	No. columns	Roll width mm	Recommended Colour ribbon	Software Article	PU pcs.
KCM-ECO 60x12	86513301	White	60 x 12	1	66	FB-TM 110 mm x 300 m	QE1	1000
KCM-ECO 60x12	86513351	Yellow	60 x 12	1	66	FB-TM 110 mm x 300 m	QE6	1000
KCM-ECO 75x15	86513300	White	75 x 15	1	81	FB-TM 110 mm x 300 m	QE0	1000
KCM-ECO 75x15	86513350	Yellow	75 x 15	1	81	FB-TM 110 mm x 300 m	QE5	1000

### Material properties



Polyethylene (PE) II

### Thermal properties



Temperature / temperature range -40 °C - 90 °C



## KCM-ECO manual cable labeling

### Technical information



Halogen-free



Silicone-free



Interior

### Classification



ETIM 9: EC001530 || eClass 14: 27281102 || UNSPSC: 39131504 ||

### General technical data



High tensile strength and tear resistance | In compliance with the requirements of REACH and RoHS



High tensile strength and tear resistance | In compliance with the requirements of REACH and RoHS

### Labelling technology



Thermal transfer