



FB-TM colour ribbon



Product information

FB-TM label ribbon made of highly resistant premium resin quality for thermal transfer printers of the mp-TM series

- Perfect print quality
- DOR black: 1.7
- Superior abrasion and scratch resistance
- Highly resistant to solvents
- Outside use
- Salt-water proof
- Antistatic

Suitable for printing of
Alpha-numerical characters or Logos
All type of barcodes

Areas of application

- Electrical and mechanical engineering
- Automobile industry
- Packaging industry
- Pharmaceutical industry
- Food industry

Storage
12 months, 5 – 35 °C
20% – 80 % rel. humidity,

Certifications

- BGA
- BS 5609
- UL tested
- EC 98/638
- Ames test
- TSCA
- California Proposition 65
- CE 1999/45/EC
- CE 2001/59/EC

Recommended for inscribing the ECP Premium and ECP ECO labels and the KC* ECO series.

Information, conformities and approvals





FB-TM colour ribbon



FB-TM colour ribbon

Article	Order No.	Color	Roll width mm	Roll length m	PU pcs.
FB-TM label colour printer ribbon - 40mm x 300m	86662004	Black	40	300	1
FB-TM label colour printer ribbon - 110mm x 300m	86662003	Black	110	300	1

Technical information



Halogen-free

Classification



ETIM 9: EC001694 || eClass 14: 19140690 || UNSPSC: 44103100 ||

Labelling technology



Thermal transfer

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.