



## Robotics kit Fanuc



### Product information

Sets specially adapted to the cable routing on robots from Fanuc. The assembly of the includes the protective conduit, end sleeves and the suitable fastening with non-slip hook-and-loop tape. For an easier installation of pre-assembled cables, the protective conduit is available in slit LS. The set offers a lowest possible interference contour for a low risk of damage.

Optional accessories:

- R-SSR - tension clamp for axis 6
- SH-P M25-M32 - system holder
- KEG/ZL or KEG/K - strain relief

### Information, conformities and approvals



Article	Order No.	Color	Corrugated conduit	Corrugated conduit size	Corrugated conduit length m	Condition	Diameter inside mm	Diameter outside mm	PU pcs.
Fixing kit for Fanuc CRX-5iA - 10iA/L									
FHS-C Set Fanuc CRX 5iA - 10iA/L 1)	83693601	Black / Red	EWX-PP-LS	M32/P29	2.5	slotted	22.6	34.2	1
Mounting kit for Fanuc CRX-10iA/L									
FHS-RS Set Fanuc CRX 10iA/L 2)	83693602	Black / Red	EWX-PP-LS	M32/P29	2.5	slotted	22.6	34.2	1
Fixing kit for Fanuc CRX 20iA/L - 25iA									
FHS-C Set Fanuc CRX 20iA/L - 25iA 1)	83693603	Black / Red	EWX-PP-LS	M32/P29	3.5	slotted	22.6	34.2	1
FHS-RS Set Fanuc CRX 20iA/L - 25iA 3)	83693604	Black / Red	EWX-PP-LS	M32/P29	7	slotted	22.6	34.2	1
1) Set includes: 3.5m EWX-PP-LS M32/P29, 4x FHS-C incl. hook-and-loop tape, 2x end grommets									
2) Set includes: 4m EWX-PP-LS M32/P29, 1x spring-retraction system, 2x FHS-SH incl. hook-and-loop tape, 1x end grommet, 1x strain relief, 1x tension clamp axis 6									
3) Set includes: 7m EWX-PP-LS M32/P29, 1x spring-retraction system, 2x FHS-SH incl. hook-and-loop tape, 1x end grommet, 1x strain relief, 1x tension clamp axis 6									

### Material properties



Polypropylene (PP) || Thermoplastic elastomer || mod. polyamide II



## Robotics kit Fanuc

### Conformity



RoHS (EC Directive 2011/65/EU)

### Approvals and operating permits



ROBI approval

### Classification



ETIM 9: EC010745 || eClass 14: 27439090 || UNSPSC: 40141764 ||