



Typ EVK




Product information

The EVK cable protection conduits are made of high-quality soft PVC with approx. 30% nitrile rubber. The integrated support coil made of rigid PVC gives the conduit a high level of dimensional stability. This makes the conduits ideal for static applications involving high mechanical loads. The EVK cable protection conduits are used mainly to protect electrical lines in machine construction and mechanical engineering and feature the following advantages:

- Excellent dimensional stability
- Hard-wearing and kink-resistant
- Weather-resistant and hard-wearing

Information, conformities and approvals



Article	Order No.	Color	A Ø mm	B Ø mm	Stat./Dyn. Radius mm	Weight kg/100m	Suitable for EH/S	Suitable for ELD/K	PU m
EVK 07/E	83301252	Black	10	13.8	10/-	9.5	M12x1,5/9		50
EVK 07	83301210	Gray	9	13.4	9/-	8.5			50
EVK 07/E	83301212	Gray	10	13.8	10/-	9.5	M12x1,5/9		25
EVK 09/E	83301216	Gray	13	17.2	13/-	12.0	M12x1,5/11	M20x1,5	50
EVK 09	83301214	Gray	14	18.8	14/-	14.0			50
EVK 11/E <sup>1)</sup>	83301220	Gray	15	19.6	15/-	15.0	PG 09/13		50
EVK 11	83301218	Gray	16	20.6	16/-	15.0	M20x1,5/13	M25x1,5	2000
EVK 13 <sup>1)</sup>	83301222	Gray	19	24	19/-	17.0			50
EVK 16	83301224	Gray	20	24.6	20/-	21.0			50
EVK 21/E <sup>1)</sup>	83301228	Gray	22	26.6	22/-	23.0	M25x1,5/21	M32x1,5	50
EVK 21	83301226	Gray	27	32.2	27/-	25.0			50
EVK 21 without print 83980141		Gray	27	32.2	27/-	28.0			50
EVK 29/E	83301232	Gray	30	35.8	30/-	30.0		M40x1,5	25



## Typ EVK

Article	Order No.	Color	A Ø mm	B Ø mm	Stat./Dyn. Radius mm	Weight kg/100m	Suitable for EH/S	Suitable for ELD/K	PU m
EVK 29	83301230	Gray	35	40.4	35/-	39.0			25
EVK 36/E	83301236	Gray	38	43.8	38/-	44.0	M40x1,5/36	M50x1,5	25
EVK 36 <sup>1)</sup>	83301234	Gray	45	51.2	45/-	51.0			25
EVK 42 <sup>1)</sup>	83301238	Gray	50	56.6	50/-	59.0	M50x1,5/48	M63x1,5	25
EVK 48 <sup>1)</sup>	83301240	Gray	55	62.2	55/-	65.0			25

<sup>1)</sup> No stock goods, delivery time and minimum order quantities upon request

### Material properties



Polyvinyl chloride (PVC) II



High angle consistency>310 N>550 N50 x 50 mm100 x 100 mm According to IEC EN 61386According to IEC EN 61386 EVK 21EL 21 Testing at 23 °CTesting at 23 °C

### Thermal properties



Temperature / temperature range -15 °C – 60 °C

### Fire properties



Fire classificationacc. to UL94: V2 self-extinguishing

### Chemical resistances



Resistant to:AlcoholLyesFuelsWeak acids

### Conformity



RoHS (EC Directive 2011/65/EU)

### Classification



ETIM 9: EC001177 || eClass 14: 27430304 || UNSPSC: 39131706 ||

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described. The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described. A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information. All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge. They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose. Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information. Murrplastik accepts no liability for damage caused as a result of using our products. Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services. Our General Terms and Conditions apply.