



Auxiliary
contactor
BGF00

Product designation

Product type designation

Contact characteristics

Number of poles	Nr.	4
Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	6
Operational frequency	min	Hz 25
	max	Hz 400
IEC Conventional free air thermal current I_{th}	A	10
Short-time allowable current for 10s (IEC/EN60947-1)	A	0
Protection fuse	gG (IEC)	A 16
Tightening torque for terminals	min	Nm 0.8
	max	Nm 1
	min	Ibin 9
	max	Ibin 9
Tightening torque for coil terminal	min	Nm 0.8
	max	Nm 1
	min	Ibin 9
	max	Ibin 9
Max number of wires simultaneously connectable	Nr.	2

Conductor section

AWG/Kcmil

	max	12
Flexible w/o lug conductor section	min	mm ² 0.75
	max	mm ² 2.5
Flexible c/w lug conductor section	min	mm ² 1.5
	max	mm ² 2.5
Flexible with insulated spade lug conductor section	min	mm ² 1.5
	max	mm ² 2.5

Power terminal protection according to IEC/EN 60529

IP20 when
properly wired

Mechanical features

Operating position

normal
allowable

Vertical plan
±30°

Fixing

Screw / DIN rail
35mm

Weight	g		180		
Auxiliary contact characteristics					
Thermal current I _{th}	A		10		
IEC/EN 60947-5-1 designation	A600 - Q600				
Operating current AC15	230V	A	3		
	400V	A	1.9		
	500V	A	1.4		
Operating current DC12	110V	A	2.9		
Operating current DC13	24V	A	2.9		
	48V	A	1.4		
	60V	A	1.1		
	125V	A	0.3		
	220V	A	0.1		
	600V	A	0.6		
Operations					
Mechanical life	cycles		20000000		
Safety related data					
Performance level B10d according to EN/ISO 13489-1	mechanical load	cycles	20000000		
EMC compatibility	yes				
AC coil operating					
Rated AC voltage at 50/60Hz	V		400		
AC operating voltage					
of 50/60Hz coil powered at 50Hz	pick-up	min	%Us	75	
		max	%Us	115	
	drop-out	min	%Us	20	
		max	%Us	55	
	of 50/60Hz coil powered at 60Hz	pick-up	min	%Us	80
			max	%Us	115
		drop-out	min	%Us	20
			max	%Us	55
		AC average coil consumption at 20°C			
		of 50/60Hz coil powered at 50Hz	in-rush	VA	30
			holding	VA	4
		of 50/60Hz coil powered at 60Hz	in-rush	VA	25
holding			VA	3	
of 60Hz coil powered at 60Hz		in-rush	VA	30	
		holding	VA	4	
Dissipation at holding ≤20°C 50Hz		W		0.95	
Max cycles frequency					
Mechanical operation	cycles/h		3600		

Operating times

Average time for Us control

in AC

Closing NO

min	ms	12
max	ms	21

Opening NO

min	ms	9
max	ms	18

Closing NC

min	ms	17
max	ms	26

Opening NC

min	ms	7
max	ms	17

in DC

Closing NO

min	ms	18
max	ms	25

Opening NO

min	ms	2
max	ms	3

Closing NC

min	ms	3
max	ms	5

Opening NC

min	ms	11
max	ms	17

UL technical data

Rated operational voltage AC (UL) V 600

Contact rating of auxiliary contacts according to UL A600 - Q600

Ambient conditions

Temperature

Operating temperature

min	°C	-50
max	°C	+70

Storage temperature


min	°C	-60
max	°C	+80

Max altitude m 3000


Resistance & Protection

Pollution degree 3

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 60947-1
CSA C22.2 n° 60947-5-1
IEC/EN 60947-1
IEC/EN 60947-5-1
UL 60947-1
UL 60947-5-1

Certificates

CCC
cULus
EAC

ETIM classification

ETIM 8.0

EC000196 -
Contactor relay