

STAR-DELTA STARTER, ENCLOSED STARTER, WITH SWITCH DISCONNECTOR, ROTARY DOOR COUPLING HANDLE GAX61 AND START AND STOP/RESET BUTTONS. STARTING TIME UP TO 12 SECONDS AND A MAXIMUM OF 30 OPERATIONS/HOUR, MAX IEC OPERATING CURRENT 60A. COIL VOLTAGE 400VAC 50/60HZ



Product designation

Enclosed star-delta starters

Product type designation

M3P03273

Electrical features

Maximum operating current ($\leq 440V$)	A	60
---	---	----

Components

Starter enclosure standard supplied	M3PA70
-------------------------------------	--------

Contactor standard supplied	BF3800A, BF3800A, BF2510A
-----------------------------	---------------------------------

Thermal relay to purchase separately	RF38...
--------------------------------------	---------

Auxiliary contact standard supplied	BFX1020, BFX1011, BFX1011
-------------------------------------	---------------------------------

Mechanical features

Weight	g	4300
--------	---	------

Ambient conditions

Operating temperature	min	°C	-25
	max	°C	+60

Storage temperature	min	°C	-40
	max	°C	+70

Resistance & Protection

Frontal IP degree	IP65
-------------------	------

ETIM classification

ETIM 8.0

EC001037 -
Motor
starter/Motor
starter
combination