




|                                                        |  |  |  |                                      |
|--------------------------------------------------------|--|--|--|--------------------------------------|
| Product designation                                    |  |  |  | Rotary cam switches                  |
| Product type designation                               |  |  |  | 7GN63                                |
| General characteristics                                |  |  |  |                                      |
| Switching diagram                                      |  |  |  | 136 - Multi-step 0-1-2-3 3 poles     |
| N° of elements                                         |  |  |  | 5                                    |
| Mounting form                                          |  |  |  | U - Front mounting with black handle |
| Contact characteristics                                |  |  |  |                                      |
| Rated insulation voltage Ui                            |  |  |  |                                      |
|                                                        |  |  |  | IEC/EN V 690                         |
|                                                        |  |  |  | UL/CSA V 600                         |
| Rated impulse withstand voltage Uimp                   |  |  |  | kV 6                                 |
| Conventional free air thermal current Ith              |  |  |  |                                      |
|                                                        |  |  |  | IEC/EN A 63                          |
|                                                        |  |  |  | UL/CSA A 60                          |
| Rated operational voltage                              |  |  |  | V 480                                |
| Rated operational impulse voltage                      |  |  |  | kV 4                                 |
| Maximum fuse size for short-circuit protection In (gG) |  |  |  |                                      |
|                                                        |  |  |  | 10kA A 63                            |
|                                                        |  |  |  | 15kA A 63                            |
|                                                        |  |  |  | 25kA A 63                            |
|                                                        |  |  |  | 50kA A 63                            |
|                                                        |  |  |  | 63kA A 63                            |
| Rated short time current Icw                           |  |  |  |                                      |
|                                                        |  |  |  | 1s kA 1600                           |
| Conductivity                                           |  |  |  | 10/5 mA/V                            |
| Operational current Ie IEC/EN                          |  |  |  |                                      |
| AC1/AC21A                                              |  |  |  |                                      |
|                                                        |  |  |  | A 63                                 |
| AC15                                                   |  |  |  |                                      |
|                                                        |  |  |  | 110V A 32                            |
|                                                        |  |  |  | 220/230V A 25                        |
|                                                        |  |  |  | 380/400V A 15                        |
|                                                        |  |  |  | 660/690V A 4                         |
| Rated operational power in AC                          |  |  |  |                                      |
| Three-phase AC-3                                       |  |  |  |                                      |
|                                                        |  |  |  | 220/230V kW 11                       |
|                                                        |  |  |  | 380/440V kW 18.5                     |
|                                                        |  |  |  | 500/690V kW 18.5                     |
| Single-phase AC-3                                      |  |  |  |                                      |
|                                                        |  |  |  | 110V kW 3.7                          |
|                                                        |  |  |  | 220/230V kW 6.5                      |
|                                                        |  |  |  | 380/440V kW 11.5                     |
| Three-phase AC23A                                      |  |  |  |                                      |
|                                                        |  |  |  | 220/230V kW 12.5                     |
|                                                        |  |  |  | 380/440V kW 30                       |
|                                                        |  |  |  | 500/690V kW 30                       |
| Single-phase AC23A                                     |  |  |  |                                      |
|                                                        |  |  |  | 110V kW 3.7                          |
|                                                        |  |  |  | 220/230V kW 7.5                      |

|                                        |  |          |                 |                   |
|----------------------------------------|--|----------|-----------------|-------------------|
|                                        |  | 380/440V | kW              | 12.5              |
| Rated operational current in DC        |  |          |                 |                   |
| DC21A                                  |  |          |                 |                   |
|                                        |  | 48V      | A               | 63                |
|                                        |  | 60V      | A               | 50                |
|                                        |  | 110V     | A               | 8                 |
|                                        |  | 220V     | A               | 1                 |
| DC23A (poles in series)                |  |          |                 |                   |
|                                        |  | 24V      | A               | 50 (1)            |
|                                        |  | 48V      | A               | 50 (2)            |
|                                        |  | 60V      | A               | 50 (3)            |
|                                        |  | 110V     | A               | 25 (3)            |
|                                        |  | 220V     | A               | 15 (4)            |
| DC13                                   |  |          |                 |                   |
|                                        |  | 24V      | A               | 63                |
|                                        |  | 48V      | A               | 40                |
|                                        |  | 60V      | A               | 28                |
|                                        |  | 110V     | A               | 3.3               |
| Power dissipation                      |  |          | W               | 3.4               |
| Mechanical features                    |  |          |                 |                   |
| Terminals screw                        |  |          |                 | M5                |
| Tightening torque for terminals max    |  |          | Nm              | 2                 |
| Conductor size                         |  |          |                 |                   |
| AWG - Rigid cable                      |  |          |                 |                   |
|                                        |  | min      | AWG             | 14                |
|                                        |  | Max      | AWG             | 6                 |
| AWG - Flexible cable                   |  |          |                 |                   |
|                                        |  | min      | AWG             | 14                |
|                                        |  | Max      | AWG             | 8                 |
| Conductor size (IEC) - Flexible cable  |  |          |                 |                   |
|                                        |  | min      | mm <sup>2</sup> | 2.5               |
|                                        |  | Max      | mm <sup>2</sup> | 10                |
| Conductor size (IEC) - Rigid cable     |  |          |                 |                   |
|                                        |  | min      | mm <sup>2</sup> | 2.5               |
|                                        |  | Max      | mm <sup>2</sup> | 16                |
| Mechanical life                        |  |          | cycles          | 5x10 <sup>6</sup> |
| UL technical data                      |  |          |                 |                   |
| Motor power for direct-on-line control |  |          |                 |                   |
| for three-phase motor                  |  |          |                 |                   |
|                                        |  | 120V     | HP              | 7.5               |
|                                        |  | 240V     | HP              | 15                |
|                                        |  | 480V     | HP              | 25                |
|                                        |  | 600V     | HP              | 25                |
| for single-phase motor                 |  |          |                 |                   |
|                                        |  | 120V     | HP              | 3                 |
|                                        |  | 240V     | HP              | 10                |
| Ambient conditions                     |  |          |                 |                   |
| Temperature                            |  |          |                 |                   |
| Operating temperature                  |  |          |                 |                   |
|                                        |  | min      | °C              | -25               |
|                                        |  | max      | °C              | +55               |
| Storage temperature                    |  |          |                 |                   |
|                                        |  | min      | °C              | -40               |
|                                        |  | max      | °C              | +70               |

## Resistance & Protection

|                     |      |
|---------------------|------|
| Frontal IP degree   | IP40 |
| Terminals IP degree | IP00 |



## Dimensions



Standard drillings for 7GN125.  
Drillings on request for 4 screws fixing  
(4V version).

| Series | Dimensions |      |    |     |     |      |      |    |    | L Number of elements |      |       |       |       |       |       |       |       |       |       |       |
|--------|------------|------|----|-----|-----|------|------|----|----|----------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|        | □A         | C    | ØD | ØD1 | ØD2 | E    | ØG   | □K | □N | 1                    | 2    | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    |
| 7GN12  | 48         | 39.5 | 39 | 12  | 5   | 26.5 | 38   | 36 | 6  | 36.1                 | 45.8 | 55.5  | 65.2  | 74.9  | 84.6  | 94.3  | 104   | 113.7 | 123.4 | 133.1 | 142.8 |
| 7GN20  | 48         | 39.5 | 39 | 12  | 5   | 26.5 | 38   | 36 | 6  | 36.1                 | 45.8 | 55.5  | 65.2  | 74.9  | 84.6  | 94.3  | 104   | 113.7 | 123.4 | 133.1 | 142.8 |
| 7GN25  | 48         | 39.5 | 43 | 12  | 5   | 26.5 | 38   | 36 | 6  | 40.5                 | 54.1 | 67.7  | 81.3  | 94.9  | 108.5 | 122.1 | 135.7 | 147.3 | 162.9 | 176.5 | 190.1 |
| 7GN32  | 65         | 53   | 58 | 14  | 5   | 34.5 | 58.5 | 48 | 7  | 46.5                 | 61.6 | 76.7  | 91.8  | 106.9 | 122   | 137.1 | 152.2 | 167.3 | 182.4 | 197.5 | 212.6 |
| 7GN40  | 65         | 53   | 58 | 14  | 5   | 34.5 | 58.5 | 48 | 7  | 46.5                 | 61.6 | 76.7  | 91.8  | 106.9 | 122   | 137.1 | 152.2 | 167.3 | 182.4 | 197.5 | 212.6 |
| 7GN63  | 65         | 53   | 62 | 14  | 5   | 34.5 | 58.5 | 48 | 7  | 50.3                 | 68.4 | 86.5  | 104.6 | 122.7 | 140.8 | 158.9 | 177   | 195.1 | 213.2 | 231.3 | 249.4 |
| 7GN125 | 90         | 70.5 | 86 | 16  | 6   | 41.5 | 84   | 68 | 9  | 67.3                 | 96.4 | 125.5 | 154.6 | 183.7 | 220.3 | 249.4 | 278.5 | 307.6 | 336.7 | 365.8 | 394.9 |

## Wiring diagrams



## Certifications and compliance

### Compliance

CSA C22.2 n° 14  
IEC/EN/BS 60947-1  
IEC/EN/BS 60947-3  
IEC/EN/BS 60947-5-1  
UL60947-4-1

### Certificates

cCSAus  
EAC  
UL

## ETIM classification

ETIM 8.0

EC001029 -  
Selector switch,  
complete