

Product designation			Rotary cam switches	
Product type designation			GX20	
General characteristics				
Switching diagram			109 - Multi-step 0-1-2-3-4 1 pole	
N° of elements			2	
Mounting form			O48 - Modular service cover for 35mm din rail mounting with black handle	
Contact characteristics				
Rated insulation voltage Ui			IEC/EN V	690
			UL/CSA V	600
Rated impulse withstand voltage Uimp			kV	6
Conventional free air thermal current Ith			IEC/EN A	20
			UL/CSA A	15
Rated operational voltage			V	440
Rated operational impulse voltage			kV	4
Maximum fuse size for short-circuit protection In (gG)			10kA A	20
			15kA A	20
			25kA A	20
Rated short time current Icw			1s kA	250
Conductivity			10/5 mA/V	
Operational current Ie IEC/EN				
AC1/AC21A			A	20
AC15			110V A	10
			220/230V A	8
			380/400V A	6
			660/690V A	1.5
Rated operational power in AC				
Three-phase AC-3			220/230V kW	3.7
			380/440V kW	5.5
			500/690V kW	5.5
Single-phase AC-3			110V kW	0.75
			220/230V kW	1.8
			380/440V kW	3
Three-phase AC23A			220/230V kW	4
			380/440V kW	7.5
			500/690V kW	7.5
Single-phase AC23A			110V kW	0.75
			220/230V kW	2.2

		380/440V	kW	3.5
Rated operational current in DC				
DC21A				
		48V	A	20
		60V	A	20
		110V	A	4
		220V	A	0.6
		440V	A	0.25
DC23A (poles in series)				
		24V	A	20 (1)
		48V	A	20 (2)
		60V	A	20 (3)
		110V	A	10 (3)
		220V	A	8 (4)
DC13				
		24V	A	20
		48V	A	16
		60V	A	12
		110V	A	1
		220V	A	0.4
		440V	A	0.15
Power dissipation			W	0.6
Mechanical features				
Terminals screw				M3
Tightening torque for terminals max			Nm	0.8
Conductor size				
AWG - Rigid cable				
		min	AWG	20
		Max	AWG	12
AWG - Flexible cable				
		min	AWG	20
		Max	AWG	12
Conductor size (IEC) - Flexible cable				
		min	mm ²	0.5
		Max	mm ²	2.5
Conductor size (IEC) - Rigid cable				
		min	mm ²	0.5
		Max	mm ²	2.5
Mechanical life			cycles	1X10 ⁶
UL technical data				
Motor power for direct-on-line control				
for three-phase motor				
		120V	HP	1.5
		240V	HP	3
		480V	HP	5
		600V	HP	5
for single-phase motor				
		120V	HP	0.75
		240V	HP	1.5
Ambient conditions				
Temperature				
Operating temperature				
		min	°C	-25
		max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70


Resistance & Protection

Frontal IP degree IP65

Terminals IP degree IP20

Dimensions

Wiring diagrams



0				
1	X			
2			X	
3		X		
4				X

109

Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-3

IEC/EN/BS 60947-5-1

IEC/EN/BS 61058-1

UL60947-4-1

Certificates

cULus

EAC

ETIM classification

ETIM 8.0

EC001029 -
Selector switch,
complete