

Product designation			Rotary cam switches	
Product type designation			GN315	
General characteristics				
Switching diagram			08 - ON/OFF switch 4 poles	
N° of elements			2	
Mounting form			O - Rear mounting with black handle	
Contact characteristics				
Rated insulation voltage Ui			IEC/EN V	690
			UL/CSA V	600
Rated impulse withstand voltage Uimp			kV	8
Conventional free air thermal current Ith			IEC/EN A	315
			UL/CSA A	255
Rated operational voltage			V	690
Rated operational impulse voltage			kV	6
Maximum fuse size for short-circuit protection In (gG)			10kA A	315
			15kA A	315
Rated short time current Icw			1s kA	5200
Operational current Ie IEC/EN AC1/AC21A			A	315
Rated operational power in AC Three-phase AC-3			220/230V kW	37
			380/440V kW	55
			500/690V kW	69
Single-phase AC-3			110V kW	11
			220/230V kW	22
			380/440V kW	30
Rated operational current in DC DC21A			48V A	200
			60V A	200
			110V A	35
			220V A	2.5
			440V A	0.9
Power dissipation			W	64.5
Mechanical features				
Terminals screw			M10	
Tightening torque for terminals max			Nm	10
Conductor size			AWG - Rigid cable	
			Max	AWG 1XMCM350
AWG - Flexible cable			Max	AWG 1XMCM350

Conductor size (IEC) - Flexible cable

Max mm² 1X185

Conductor size (IEC) - Rigid cable

Max mm² 1X185

Mechanical life

cycles 2X10⁵

UL technical data

Motor power for direct-on-line control

for three-phase motor

120V	HP	30
240V	HP	50
480V	HP	100
600V	HP	75

for single-phase motor

120V	HP	15
240V	HP	30

Ambient conditions

Temperature

Operating temperature

min	°C	-25
max	°C	+55

Storage temperature

min	°C	-40
max	°C	+70

Resistance & Protection


Frontal IP degree

IP40

Terminals IP degree

IP00


Dimensions



Series	Dimensions									L Number of elements ①											
	□A	C	ØD2	E	I	□K	□N	P	ØT	1	2	3	4	5	6	7	8	9	10	11	12
GN200	132	104	5.3	56	20	104	10	140	10.5	77	107	136	166	196	226	284	314	343	373	402	432
GN315	132	104	5.3	56	20	104	10	145	10.5	77	107	136	166	196	226	284	314	343	373	402	432

① For devices with 6 or more elements please contact please consult Technical support, see contact details on inside front cover.

Wiring diagrams



Certifications and compliance

Compliance

IEC/EN/BS 60947-1
IEC/EN/BS 60947-3
IEC/EN/BS 60947-5-1
UL60947-4-1

Certificates

UR

ETIM classification

ETIM 8.0	EC001029 - Selector switch, complete
----------	--------------------------------------