

Product designation				Enclosed rotary cam switch
Product type designation				7GN25
General characteristics				
Switching diagram				53 - Changeover switch 3 poles - 2 speed motor starting with separate windings
N° of elements				3
Mounting form				P25 - Plastic enclosure with red/yellow handle
Contact characteristics				
Rated insulation voltage Ui		IEC/EN UL/CSA	V V	690 600
Rated impulse withstand voltage Uimp			kV	6
Conventional free air thermal current Ith		IEC/EN UL/CSA	A A	25 30
Rated operational voltage			V	480
Rated operational impulse voltage			kV	4
Maximum fuse size for short-circuit protection In (gG)		10kA 15kA 25kA	A A A	25 25 25
Rated short time current Icw		1 s	kA	400
Conductivity	10/5 mA/V			
Operational current Ie IEC/EN				
AC1/AC21A			A	25
AC15		110V 220/230V 380/400V 660/690V	A A A A	16 12 8 2
Rated operational power in AC				
Three-phase AC-3		220/230V 380/440V 500/690V	kW kW kW	5.5 7.5 7.5
Single-phase AC-3		110V 220/230V 380/440V	kW kW kW	1.5 3 5.5
Three-phase AC23A		220/230V 380/440V 500/690V	kW kW kW	6.5 11 11
Single-phase AC23A		110V	kW	1.5

		220/230V	kW	3.7
		380/440V	kW	5.5
Rated operational current in DC				
DC21A				
		48V	A	25
		60V	A	25
		110V	A	4
		220V	A	0.7
DC23A (poles in series)				
		24V	A	25 (1)
		48V	A	25 (2)
		60V	A	25 (3)
		110V	A	12 (3)
		220V	A	10 (4)
DC13				
		24V	A	25
		48V	A	20
		60V	A	16
		110V	A	1.5
		220V	A	0.4
Power dissipation			W	1.1
Mechanical features				
Terminals screw			M3.5	
Tightening torque for terminals max			Nm	0.8
Conductor size				
AWG - Rigid cable				
		min	AWG	20
		Max	AWG	10
AWG - Flexible cable				
		min	AWG	20
		Max	AWG	12
Conductor size (IEC) - Flexible cable				
		min	mm ²	0.5
		Max	mm ²	4
Conductor size (IEC) - Rigid cable				
		min	mm ²	0.5
		Max	mm ²	4
Mechanical life			cycles	5x10 ⁶
UL technical data				
Motor power for direct-on-line control				
for three-phase motor				
		120V	HP	3
		240V	HP	5
		480V	HP	10
		600V	HP	15
for single-phase motor				
		120V	HP	1.5
		240V	HP	3
Ambient conditions				
Temperature				
Operating temperature				
		min	°C	-25
		max	°C	+55
Storage temperature				

ENCLOSED ROTARY CAM SWITCH 7GN SERIES, 2 SPEED MOTOR STARTING WITH
SEPARATE WINDINGS 25A IN PLASTIC ENCLOSURE 90X90 WITH RED/YELLOW HANDLE

min	°C	-40
max	°C	+70

Resistance & Protection

Frontal IP degree	IP65
-------------------	------

Terminals IP degree	IP00
---------------------	------

ETIM classification

ETIM 8.0	EC001029 - Selector switch, complete
----------	--