



Product designation

Product type designation

Number of poles

Operating voltage type

Changeover
Switch
GE
Nr. 4
AC

Contact characteristics

IEC Conventional free air thermal current I _{th}	A	200
Rated insulation voltage U _i IEC/EN	V	1000
Rated impulse withstand voltage U _{imp}	kV	8

Operating current I_e

AC21A

400V	A	200
500V	A	200
690V	A	200

AC22A

400V	A	200
500V	A	200
690V	A	160

AC23A

400V	A	160
500V	A	125

Power dissipation per pole max	W	8
--------------------------------	---	---

Rated operational power AC23A

400V	kW	100
690V	kW	69

Rated short time current (1s) I _{cw} (rms)	kA	8
---	----	---

Conditional short-circuit current (rms)	kA	100
---	----	-----

Short-circuit protection with fuse	Class/A	gG200
------------------------------------	---------	-------

Making capacity AC23A 400V	A	3150
----------------------------	---	------

Mechanical life	cycles	10000
-----------------	--------	-------

Electrical life AC21A	cycles	1000 (AC23A 400V)
-----------------------	--------	-------------------

Mechanical features

Operating position

normal
allowable
Vertical plan
Any

Fixing	Screw
--------	-------

Terminals	type screw	Bar M10
-----------	---------------	------------

Tightening torque for terminals

max	Nm	24
max	lbin	18

Bar dimensions max	25x3
--------------------	------

Ambient conditions

Operating temperature

min	°C	-25
max	°C	55

Storage temperature

min	°C	-40
max	°C	70

Max altitude

m	3000
---	------

Resistance & Protection


Frontal IP degree

IP20

Pollution degree

3


Dimensions



TYPE	A	B	C	D	ØE	F	G	H	J	K	L	M	N	O	P	Q	R Max	S	Ø T	U	V	Shaft extension	Terminal covers (N° of pcs/set)		
																						W	X (line 1)	Y (line 2)	Z (load)
GE0201 E GE0250 E GE0315 E GE0400 E	235 (9.25")	119.5 (4.70")	115.5 (4.55")	25 (0.98")	5.5 (0.22")	157 (6.18")	192 (7.56")	216 (8.50")	45 (1.77")	88 (3.46")	357 (14.05")	170 (6.69")	42 (1.65")	3 (0.12)	67 (2.64")	151 (5.94")	437 (17.2")	143 (5.63")	M10	133 (5.24")	142 (5.59")	GEX7227N GEX7375N GEX7536N □ 10 (0.6")	GEX82 12 (3)	GEX82 11 (3)	GEX83 12 (3)
GE0201 ET4 GE0250 ET4 GE0315 ET4 GE0400 ET4																							GEX82 13 (4)	GEX82 13 (4)	GEX83 12 (4)
GE0500 E GE0630 E GE0800 E																							GEX82 22 (3)	GEX82 21 (3)	GEX83 21 (3)
GE0500 ET4 GE0630 ET4 GE0800 ET4																									

Wiring diagrams

GE0201 ET4 - GE1600 ET4



Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-3

Certifications

EAC

ETIM classification

ETIM 8.0

EC000216 -
Switch
disconnecter