



# Label plate KSM (Polypropylene) / KSM-D (Polypropylene)




## Product information

High-quality label to attach with cable ties directly onto the cables. The KSM labels are a product that is used for the subsequent labeling. Also available as easily detectable KSM-D labels. The detectability is realized by iron dust, which is detectable either electromagnetically or radiologically. The material Polypropylene (PP) is intended only for labels created with the MP laser system.

The KSM PP-V0 articles have an increased UVresistance.

## Information, conformities and approvals



Article	Order No.	Color	RAL equiv.	min Diameter mm	Label size mm (B x A)	Printable area (mm)	Number of characters / lines	Quantity per frame	Software Article	Base plate	PU pcs.
Labels for lengthways mounting; for labelling with the MP laser system											
KSM 35x8 PP-V0	86282020	Yellow	1018	5	8 x 35	8 x 18	10 / 2	16	529	GP3M	320
KSM 35x8 PP-V0	86282010	White	9016	5	8 x 35	8 x 18	10 / 2	16	524	GP3M	320
KSM 45x10 PP-V0	86282022	Yellow	1018	5	10 x 45	10 x 28	15 / 2	8	530	GP3M	160
KSM 45x10 PP-V0	86282012	White	9016	5	10 x 45	10 x 28	15 / 2	8	525	GP3M	160
KSM 55x12 PP-V0	86282024	Yellow	1018	5	12 x 55	12 x 38	21 / 3	6	531	GP3M	108
KSM 55x12 PP-V0	86282014	White	9016	5	12 x 55	12 x 38	21 / 3	6	526	GP3M	108
KSM 65x14 PP-V0	86282028	Yellow	1018	5	14 x 65	14 x 48	26 / 4	6	533	GP3M	108
KSM 65x14 PP-V0	86282018	White	9016	5	14 x 65	14 x 48	26 / 4	6	528	GP3M	108
KSM 70x10 PP-V0	86282026	Yellow	1018	5	10 x 70	10 x 53	29 / 2	8	532	GP3M	144
KSM 70x10 PP-V0	86282016	White	9016	5	10 x 70	10 x 53	29 / 2	8	527	GP3M	144

## Detectable cable ties for lengthways mounting; for labelling with the MP laser system



## Label plate KSM (Polypropylene) / KSM-D (Polypropylene)

Article	Order No.	Color	RAL equiv.	min Diameter mm	Label size mm (B x A)	Printable area (mm)	Number of characters / lines	Quantity per frame	Software Article	Base plate	PU pcs.
KSM-D 35x8 PP	86281810	Gray	7038	5	8 x 35	8 x 18	10 / 2	16	534	GP3M	320
KSM-D 45x10 PP	86281812	Gray	7038	5	10 x 45	10 x 28	15 / 2	8	535	GP3M	160
KSM-D 55x12 PP	86281814	Gray	7038	5	12 x 55	12 x 38	21 / 3	6	536	GP3M	108
KSM-D 65x14 PP	86281818	Gray	7038	5	14 x 65	14 x 48	26 / 4	6	538	GP3M	108
KSM-D 70x10 PP	86281816	Gray	7038	5	10 x 70	10 x 53	29 / 2	8	537	GP3M	144

### Material properties



Polypropylene (PP) II

### Thermal properties



Temperature / temperature range -30 °C – 90 °C

### Fire properties



Fire classification HBV0 PP-V0 only

### Technical information



Halogen-free

### Classification



ETIM 9: EC001530 || eClass 14: 27281102 || UNSPSC: 39131504 ||

### General technical data



Single-line and multi-line labelling



Single-line and multi-line labelling



## Label plate KSM (Polypropylene) / KSM-D (Polypropylene)

### Assembly method



Cable tie system with plate

### Labelling technology



Laser