





LAM Rectangular without radius, 2x oblong hole



Product information

Laser Alumat consists of coated aluminum, suitable for laser engraving. The surface is coated for laser engraving. After laser marking with a Murrplastik mp-LM series laser marking system the engraving appears in black. Available in a material thickness of 0.5 mm or 1.0 mm.

A suction and filter unit is absolutely necessary to comply with legal regulations on health protection.


Information, conformities and approvals



Article	Order No.	Color	Material thickness mm	Printable area mm	No. characters/lines	Hole patterns Number x Ø mm	No. per Frame	Software Article	PU pcs.
Rectangular design with corner radius and 2 slots									
LAM 37x9 HF, 2x (2,8x5MM)	8610140423	Yellow matte	1	26 x 9	14 / 2	2x	20	PAE	80
Rectangular design with 2 slots									
LAM 70x35 HF, 2x (10,3x5,4MM)	8610140025	Silver	0.5	39 x 35	21 / 10	2x	3	LF8	12



LAM Rectangular without radius, 2x oblong hole



Laser labelling material dimensions table

Article	Order No.	Drill hole pitch X mm	Drill hole position X1 mm	Drill hole position Y1 mm	Drill hole position X2 mm
Rectangular design with corner radius and 2 slots					
LAM 37x9 HF, 2x (2,8x5MM)	8610140423	31	3	4.5	37
Rectangular design with 2 slots					
LAM 70x35 HF, 2x (10,3x5,4MM)	8610140025	54.7	7.65	17.5	62.35

Material properties



Aluminium painted (ALU) |

Adhesive properties



467, 5016 SK adhesive film with adhesive, SKS adhesive film with foam adhesive

Thermal properties



Temperature / temperature range -20 °C – 80 °C
short termshort term: 120 °C

Fire properties



Fire classification V0

General technical data

° Standard product, available from stock



LAM Rectangular without radius, 2x oblong hole

Assembly method



Riveting system



Screw system

Labelling technology



Laser