




ALU Rectangular without radius, 2x hole



Product information

The ALU labelling material, in mat size 300x200 mm, has been developed especially for engraving.

- Coloured anodised aluminium material
- Available with self-adhesive foil / adhesive foil
- Individual or prefab labels
- Temperature range up to approx. 200 °C
- Thickness: 1.0 mm
- marking technique: Engraving

Material thickness mm: 1

Information, conformities and approvals



Article	Order No.	Color	Label size mm	Number x Holes mm	Quantity per mat	Software Article	PU pcs.
Without corner radius; with adhesive foil							
ALU 10x40 HF, 2x2.5MM ¹⁾	8604226046	Silver anodized	10 x 40	2x 2.5	150	M62	150
ALU 15x40 HF, 2x3.0MM ¹⁾	8604226042	Silver anodized	15 x 40	2x 3.0	100	H54	100
ALU 15x80 HF, 2x2.5MM ¹⁾	8604226013	Black anodized	15 x 80	2x 2.5	39	665	40
ALU 25x65 HF, 2x4.0MM ¹⁾	8604226048	Red anodized	25 x 65	2x 4.0	36	M91	33
ALU 26x80 HF, 2x2.5MM ¹⁾	8604226045	Silver anodized	26 x 80	2x 2.5	22	M55	22
ALU 30x10 HF, 2x2.5MM (X=24) ¹⁾	8604226009	Silver anodized	30 x 10	2x 2.5	200	868	200
ALU 30x10 HF, 2x2.5MM (X=26) ¹⁾	8604226021	Silver anodized	30 x 10	2x 2.5	200	178	200
ALU 30x10 HF, 2x3.2MM ¹⁾	8604226011	Black anodized	30 x 10	2x 3.2	200	934	200
ALU 30x30 HF, 2x5.0MM ¹⁾	8604226047	Silver anodized	30 x 30	2x 5.0	60	M75	60



ALU Rectangular without radius, 2x hole

Article	Order No.	Color	Label size mm	Number x Holes mm	Quantity per mat	Software Article	PU pcs.
ALU 34x12 HF, 2x3.5MM ¹⁾	8604226023	Silver anodized	34 x 12	2x 3.5	128	617	128
ALU 36x10 HF, 2x2.5MM ¹⁾	8604226041	Blue anodized	36 x 10	2x 2.5	160	D42	160
ALU 37x18 HF, 2x3.2MM ¹⁾	8604226010	Silver anodized	37 x 18	2x 3.2	88	925	88
ALU 40x10 HF, 2x4.0MM ¹⁾	8604226015	Black anodized	40 x 10	2x 4.0	140	240	140
ALU 40x12 HF, 2x2.2MM ¹⁾	8604226035	Black anodized	40 x 12	2x 2.2	112	D11	112
ALU° 40x15 HF, 2x2.5MM ¹⁾	8604226000	Silver anodized	40 x 15	2x 2.5	91	484	91
ALU 40x15 HF, 2x2.5MM ¹⁾	8604226012	Black anodized	40 x 15	2x 2.5	91	409	91
ALU 40x15 HF, 2x3.3MM ¹⁾	8604226040	Black anodized	40 x 15	2x 3.3	91	D18	91
ALU 40x20 HF, 2x3.0MM ¹⁾	8604226027	Silver anodized	40 x 20	2x 3.0	70	4M	70
ALU 40x20 HF, 2x3.0MM ¹⁾	8604226008	Black anodized	40 x 20	2x 3.0	70	777	70
ALU 40x20 HF, 2x3.2MM ¹⁾	8604226020	Silver anodized	40 x 20	2x 3.2	70	137	70
ALU 40x24 HF, 2x2.2MM ¹⁾	8604226034	Black anodized	40 x 24	2x 2.2	56	D10	56
ALU 45x19 HF, 2x2.6MM ¹⁾	8604226025	Silver anodized	45 x 19	2x 2.6	60	1H	60
ALU 50x20 HF, 2x3.3MM ¹⁾	8604226039	Silver anodized	50 x 20	2x 3.3	54	D17	60
ALU 50x20 HF, 2x3.5MM ¹⁾	8604226030	Black anodized	50 x 20	2x 3.5	60	78	60
ALU° 55x20 HF, 2x2.5MM ¹⁾	8604226001	Silver anodized	55 x 20	2x 2.5	50	482	50
ALU° 55x20 HF, 2x2.5MM ¹⁾	8604226006	Black anodized	55 x 20	2x 2.5	50	748	50
ALU 55x25 HF, 2x4.0MM ¹⁾	8604226022	Silver anodized	55 x 25	2x 4.0	40	213	40
ALU 60x15 HF, 2x3.4MM ¹⁾	8604226044	Silver anodized	60 x 15	2x 3.4	65	K25	65
ALU 60x20 HF, 2x3.5MM ¹⁾	8604226028	Black anodized	60 x 20	2x 3.5	50	5H	50




ALU Rectangular without radius, 2x hole

Article	Order No.	Color	Label size mm	Number x Holes mm	Quantity per mat	Software Article	PU pcs.
ALU 60x20 HF, 2x3.5MM ¹⁾	8604226029	Blue anodized	60 x 20	2x 3.5	50	5I	50
ALU 60x25 HF, 2x3.0MM ¹⁾	8604226018	Silver anodized	60 x 25	2x 3.0	10	385	40
ALU 60x30 HF, 2x3.3MM ¹⁾	8604226036	Silver anodized	60 x 30	2x 3.3	30	D14	30
ALU 60x40 HF, 2x2.0MM ¹⁾	8604226031	Red anodized	60 x 40	2x 2.0	25	6M	25
ALU 70x10 HF, 2x2.0MM ¹⁾	8604226007	Silver anodized	70 x 10	2x 2.0	80	766	80
ALU 70x25 HF, 2x3.5MM ¹⁾	8604226032	Black anodized	70 x 25	2x 3.5	32	7I	32
ALU 70x26 HF, 2x3.3MM ¹⁾	8604226038	Silver anodized	70 x 26	2x 3.3	28	D16	28
ALU 70x27 HF, 2x2.6MM ¹⁾	8604226024	Silver anodized	70 x 27	2x 2.6	28	655	28
ALU 70x50 HF, 2x3.3MM ¹⁾	8604226037	Silver anodized	70 x 50	2x 3.3	16	D15	16
ALU 74x26 HF, 2x3.2MM ¹⁾	8604226016	Silver anodized	74 x 26	2x 3.2	28	360	28
ALU 100x40 HF, 2x2.5MM ¹⁾	8604226019	Silver anodized	100 x 40	2x 2.5	15	R3A	15
ALU 105x37 HF, 2x3.2MM ¹⁾	8604226017	Silver anodized	105 x 37	2x 3.2	10	654	10
ALU 120x80 HF, 2x6.0MM ¹⁾	8604226043	Red anodized	120 x 80	2x 6.0	4	H76	4
ALU 145x85 HF, 2x2.6MM (diagonal) ¹⁾	8604226026	Silver anodized	145 x 85	2x 2.6	4	3J	4
ALU 290x30 HF, 2x3.0MM ¹⁾	8604216001	Silver anodized	290 x 30	2x 3.0	6	780	6
Without corner radius; with self-adhesive foil							
ALU 18x200 SK, 2x3.0MM ¹⁾	8604220014	Silver anodized	18 x 200	2x 3.0	16	2J	16
ALU 25x10 SK, 2x2.2MM ¹⁾	8604220004	Silver anodized	25 x 10	2x 2.2	240	367	240
ALU 25x10 SK, 2x2.2MM ¹⁾	8604220009	Black anodized	25 x 10	2x 2.2	240	515	240
ALU 30x15 SK, 2x2.3MM ¹⁾	8604220000	Blue anodized	30 x 15	2x 2.3	130	860	130



ALU Rectangular without radius, 2x hole



Article	Order No.	Color	Label size mm	Number x Holes mm	Quantity per mat	Software Article	PU pcs.
ALU 30x15 SK, 2x2,5MM ¹⁾	8604220011	Silver anodized	30 x 15	2x 2.5	130	688	130
ALU 40x9 SK, 2x2,5MM ¹⁾	8604220001	Silver anodized	40 x 9	2x 2.5	154	988	154
ALU 50x12.5 SK, 2x3,0MM ¹⁾	8604220002	Silver anodized	50 x 12.5	2x 3.0	96	050	96
ALU 50x25 SK, 2x3,0MM ¹⁾	8604220003	Silver anodized	50 x 25	2x 3.0	48	027	48
ALU 50x25 SK, 2x3,0MM ¹⁾	8604220015	Silver anodized	50 x 25	2x 3.0	48	276	48
ALU 60x16 SK, 2x2,5MM ¹⁾	8604220007	Silver anodized	60 x 16	2x 2.5	60	193	60
ALU 70x10 SK, 2x2,2MM ¹⁾	8604220010	Black anodized	70 x 10	2x 2.2	80	536	80
ALU 90x16 SK, 2x2,5MM ¹⁾	8604220005	Silver anodized	90 x 16	2x 2.5	36	190	36
ALU 130x32 SK, 2x2,5MM ¹⁾	8604220013	Silver anodized	130 x 32	2x 2.5	12	689	12
ALU 180x32 SK, 2x2,5MM ¹⁾	8604220008	Silver anodized	180 x 32	2x 2.5	6	194	6
ALU 230x32 SK, 2x2,5MM ¹⁾	8604220006	Silver anodized	230 x 32	2x 2.5	6	191	6

¹⁾ Other sizes available on request

Engraving material Dimension table

Article	Order No.	Drill hole pitch X mm	Drill hole pitch Y mm	Drill hole position X1 mm	Drill hole position Y1 mm	Drill hole position
Without corner radius; with adhesive foil						



ALU Rectangular without radius, 2x hole

Material properties



Aluminium anodised
(ALU)

Adhesive properties



467 SK adhesive film with
adhesive

Thermal properties



Temperature / temperature
range -40 °C – 140 °C

Fire properties



Fire classification V0

General technical data



Single-line and multi-line
labelling

Assembly method



Adhesive system



Screw system

Labelling technology



Engraving